



Referencecode: 4300500



General	
Length (mm)	65
Diameter (mm)	50
Cover	Transparent
Housing Color	Grey
Housing Material	Aluminum
Weight (g)	85
Electronics	
Input Voltage	0 ~ 13.9 V DC (max)
LED nominal current at CC (mA)	700
Power Consumption (W)	9W @ 700mA
Power Supply	External
Luminous Efficacy	105 lm/W
Lighting	
Ligitting	
Optics (°)	24
	24 Cree SMD5050 XM-L 4in1
Optics (°)	<del>-</del> ·
Optics (°) LED Type	Cree SMD5050 XM-L 4in1
Optics (°) LED Type Color Range	Cree SMD5050 XM-L 4in1 RGBW
Optics (°) LED Type Color Range Color Temperature (Kelvin)	Cree SMD5050 XM-L 4in1 RGBW 3000 K
Optics (°) LED Type Color Range Color Temperature (Kelvin) Colour Rendering Index (CRI)	Cree SMD5050 XM-L 4in1 RGBW 3000 K
Optics (°) LED Type Color Range Color Temperature (Kelvin) Colour Rendering Index (CRI) Luminous Flux	Cree SMD5050 XM-L 4in1 RGBW 3000 K
Optics (°) LED Type Color Range Color Temperature (Kelvin) Colour Rendering Index (CRI) Luminous Flux Control	Cree SMD5050 XM-L 4in1 RGBW 3000 K 80 945 lm
Optics (°) LED Type Color Range Color Temperature (Kelvin) Colour Rendering Index (CRI) Luminous Flux  Control  Control Units	Cree SMD5050 XM-L 4in1 RGBW 3000 K 80 945 lm  Single pixel





**IP54** 



## Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.