

General

Product Type	Wireless
Length (mm)	145
Width (mm)	40
Height (mm)	12
Housing Color	White
Housing Material	Plastic
Weight (g)	85

Electronics

Power Supply N/A

Lighting

Color Range RGBW

Control

Output Signal	2.4 GHz
Control	Radio Frequency
Remote Distance	25m
Zones	1

Environmental

Ingress Protection	IP20
Batterv	1x CR2032

CE IP20 5 year warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.

181

oneeighty one.com





2 4G LED RGBW Controller







F4



Main Characteristics

F4 RF RGBW Remote Control

Remote Option:

RGRW

Working Voltage:

3Vdc (Battery CR2032)

Wireless Frequency: Working Temperature: -30°C~55°C

2 4GHz

Package Size:

Weight(G.W.):

L150×W46×H18(mm)

F4-3A CV Receiver

Input Voltage:

5~2/JVdc

Current Load:

3A × 4CH Max. 12A

Max Output Power:

60W/144W/288W(5V/12V/24V)

Working Temperature: -30°C~55°C

L127×W35×H24(mm)

Package Size: Weight(G.W.):

60q

F4-5A CV Receiver

Input Voltage:

5~24Vdc

Current Load:

5A × 4CH Max. 20A

Max Output Power:

100W/240W/480W(5V/12V/24V)


Working Temperature:


-30°C~55°C

Package Size:

L178×W48×H33(mm)

Note: Receiver is sold separately.





F4-CC CC Receiver

Input Voltage: Output Voltage: 12~48Vdc 3~46Vdc

Output Current:

CC 350/700/1050mA×4CH 1 05W~48 3W×4CH Max 193 2W


Output Power: Working Temperature:


-30°C~55°C


L178×W48×H33(mm) Package Size: Weight(G.W.): 165g


Weight(G.W.): 150a

Dimensions













Operating Instruction for Remote:

