



General

| | |
|------------------|-------------|
| Length (mm) | 65 |
| Diameter (mm) | 50 |
| Cover | Transparent |
| Housing Color | Grey |
| Housing Material | Aluminum |
| Weight (g) | 85 |

Electronics

| | |
|--------------------------------|---------------------|
| Input Voltage | 0 ~ 13.9 V DC (max) |
| LED nominal current at CC (mA) | 700 |
| Power Consumption (W) | 9W @ 700mA |
| Power Supply | External |
| Luminous Efficacy | 105 lm/W |

Lighting

| | |
|------------------------------|------------------------|
| Optics (°) | 24 |
| LED Type | Cree SMD5050 XM-L 4in1 |
| Color Range | RGBW |
| Color Temperature (Kelvin) | 3000 K |
| Colour Rendering Index (CRI) | 80 |
| Luminous Flux | 945 lm |

Control

| | |
|--------------------|--------------|
| Control Units | Single pixel |
| Number of Channels | 4 |

Environmental

| | |
|--------------------|------|
| Ingress Protection | IP54 |
|--------------------|------|



IP54

3 year
warranty

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.