LED Downlight 9W Module RGBW

4300500



General	
Length (mm)	65
Diameter (mm)	50
Cover	Transparent
Housing Color	Grey
Housing Material	Aluminum
Weight (g)	85
Electronics	
Input Voltage	0 ~ 13.9 V DC (max)
LED nominal current at CC (mA)	700
Power Consumption (W)	9W @ 700mA
Power Supply	External
Luminous Efficacy	105 lm/W
Lighting	
Optics (°)	24
LED Type	Cree SMD5050 XM-L 4inl
Color Range	RGBW
Color Temperature (Kelvin)	3000 K
Colour Rendering Index (CRI)	80
Luminous Flux	945 lm
Control	
Control Units	Single pixel
Number of Channels	4
Environmental	

IP54

Ingress	Protection






Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. OneEightyOne is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make technical changes to our products and to change information, at its sole discretion, without notice.


181





oneeighty

one.com



OneEightyOne Valschermkade 27 – 28 | 1059CD | Amsterdam +31 20 8200170 | info@oneeightyone.com | www.oneeightyone.com

©2024